

Offering an Outstanding 1080P Full-HD Video Conferencing Experience

The VC120 is Yealink's latest innovative 1080P full-HD video conferencing endpoint for branch offices. It is designed to provide ease-of-use, high-quality and cost-efficiency. To make life easier still, the VC120 supports an intelligent firewall traversal which allows users to plug and play with no further firewall configuration from box to work in just five-minutes. In addition, VC120 also supports bandwidth dynamic adaptive adjustment, and an 8% resistance packet loss. It is definitely the best choice for business video conferencing.



Key Features and Benefits

HD Video

The system offers 1080P30 people+content shared video conferencing. It also supports full-HD dual stream to demonstrate documents or videos, a development that significantly improves the user conferencing experience.

Optimal HD Voice

The Yealink VCS Phone has several built-in microphone arrays and supports 360 degree voice pickup. With an optional expansion microphone KIT, the voice pickup range can be extended to up to 5 metres. 20KHz CD level broadband audio quality, plus a number of new leading-edge professional voice processing technologies, guarantee users an excellent audio experience.

Outstanding User Experience

Yealink VC120 makes maximum use of its advanced features to provide an outstanding user experience. Yealink supports intelligent searching when making calls. During a call, you can adjust the screen layout as you wish. In addition, using the dual-screen display you can show whatever you like on a second screen at full size. This system also supports video recording and screenshots to record conferences more efficiently. An outstanding user experience leads to lower learning costs and higher efficiency.

High Interoperability

Yealink VC120 supports SIP and H.323 and is compatible with the industry's major system and terminal vendors, introducing an important cost-effectiveness and flexibility that helps users to expand their businesses. Interconnection is also possible with other devices, such as video phones, tablet computers and smartphones. Users can access video conferencing at anytime and anywhere at their convenience.

- 18x optical zoom PTZ camera
- Microphone arrays with 360 degree voice pickup
- H.264 high profile, saving 50% bandwidth
- Yealink intelligent firewall traversal
- Bandwidth dynamic adaptive adjustment
- Video recording and playback
- Remote diagnosis
- Dual displays and 'focus' feature
- High compatibility and interoperability

System Components

- Codec VC120
- VCS Phone VCP40
- HD PTZ Camera VCC18
- Remote control VCR10

Full-HD Camera

- 1920x1080 video resolution
- Up to 18x optical zoom PTZ camera
- Pan range: $\pm 100^\circ$
- Tilt range: $\pm 30^\circ$
- Up to 10 preset positions
- Beauty shot feature

Video Resolution

- Full-HD 1080P at 30fps (1920x1080), from 1Mbps
- 720P (1280 x 720), from 512Kbps
- W448P (768 x 448), WQVGA (400 x 240)
- 4CIF (704 x 576), CIF (352 x 288)

Video Standard and Network Suitability

- H.264 High Profile, H.264, H.263
- Bandwidth dynamic adaptive adjustment
- Forward Error Correction (FEC), anti 8% video and 20% audio packet loss
- Shared content and audio preference strategy
- Bandwidth Auto adaptive/Protocol Auto adaptive/Audio/Video call Auto adaptive

Audio Features

- 3-microphone array
- 10ft/ 3-metre and 360 degree voice pickup
- Optional 2 expansion microphones, enhancing voice pickup to 16ft/ 5-metres
- Audio Codecs: G.722.1C, G.722.1, G.722, G.711 u/a
- Audio technology: AEC, VAD, CNG, PLC, AJB, AGC

Call Features

- Dual 1080P30: people+ content sharing
- Layout: full-screen, equal, one big/one small
- Dual displays and 'focus' feature
- Audio/Video recording and playback
- Screenshots in USB flash drive
- Sleep mode, DND
- Call statistics
- Auto answer, mute, and call waiting
- Intelligent searching
- Local directory: 1000 entries
- Call History: all/ missed/ received/ dialed
- LDAP phonebook
- National language selection

Standard Communication Protocol

- H.323/SIP
- Dual stream protocol: H.239/ BFCP (SIP)
- FECC: H.224/ H.281
- H.323 protocol suite: H.225, H.241, H.245, H.235 v3
- Support gatekeeper account and SIP account

Network and Security

- TCP/ IP (IPv4), DHCP/ static IP
- HTTP/ HTTPS web server
- SRTP/ TLS, AES encryption
- QoS: 802.1p/Q, Diff-serv
- IEEE802.1X, LLDP-MED, VLAN
- Time and date synchronization using SNTP
- Built-in certificate

NAT and Firewall Transversal

- NAT (manual/ auto mode)
- Yealink intelligent firewall traversal
- OpenVPN
- H.460

Configuration Management

- Configuration via browser/ display
- Firmware upgrading, factory resetting
- Export or import configuration
- SNMP, audio/video and network diagnosis
- Package tracing and system log exporting

Codec User Interface

- 1 x 10/100/1000M Ethernet
- 2 x HDMI, 1 x DVI, 1 x VGA
- 1 x VCS phone port (RJ-45)
- 1 x Line-in (3.5mm)
- 1 x Line-out (3.5mm)
- 1 x power port, 2 x USB2.0 port
- Others: 1 x power key, 1 x security lock slot, 1 x reset slot

Other Physical Features

- External universal AC adapter: AC 100~240V input and DC 19V/3.42A Output
- Power consumption (PSU): Idle < 2.8W, normal operating: 24W; MAX: 30W
- Dimension (W.D.H):
Codec: 330mm x 183mm x 40mm;
Phone: 320mm x 260mm x 52mm;
Camera: 282mm x 152mm x 159mm;
Remote control: 190mm x 55mm x 24mm
- Operating humidity: 10~95%
- Storage temperature: -10~50°C

Package Features

- N.W/CTN: 7.2kg
- G.W/CTN: 8.4kg
- Carton Meas: 418mm x 350mm x 420mm

Certification

