

# <u>CONTROL YOUR</u> <u>COLLABORATION</u> <u>WITH EASE</u>

# **BENEFITS**

- Integrated calendar so it's easy to find your meeting and connect
- Intuitive interface makes it easy to personalize the experience for more productive meetings
- Power over Ethernet means only one cable is required, keeping your table clean
- Easy setup as it's pre-paired out of the box when purchasing as part of a full Poly video solution

# POLY TC8

This intuitive touch interface provides easy access to Poly video conferencing solutions. The sleek design features an 8" high-resolution touch display to ensure that the control options are clear and accessible. A single cable carries both power and data to reduce clutter. After using the Poly TC8, you'll never stress about getting your meeting going again. Having confidence that you can easily initiate, join, or share content lets you focus on better collaboration.

- Integrated calendar for one touch to join a call
- · Easily share content, adjust the camera, and change participant layouts
- Compatible with Poly Studio X family and Poly G7500





# **SPECIFICATIONS**

## **PACKAGE INCLUDES:**

- Poly TC8 and RJ45 (LAN) cable
- Setup sheet
- Printed warranty statement

# **PHYSICAL CHARACTERISTICS**

- Physical dimensions: 123 x 205 x 79 (mm)
- Micro-B USB 2.0 (diagnostics)
- Mechanical locking mechanism
  (Kensington lock)
- Weight: 812 grams

## **OPERATING ENVIRONMENT**

- Temperature: 0°C to 40°C
- Non-operating: -20°C to 60°C

### ALTITUDE

- Operating: 0 to 10,000 ft ASL
- Non-operating: 0 to 35000 ft ASL

#### **COMPATIBLE SYSTEMS**

- Poly G7500 (min 3.0 software)
- Poly Studio X30 and Studio X50

#### USABILITY

- Display: 8-inch screen
- Aspect ratio: 16 x 10
- Resolution: WXGA (1280 x 800)
- Designed with built-in stand support-no external stand required

- Viewing angle: 75 degrees (U/D/L/R)
- Positioning/placing angle: 60 degrees
- Tap and touch control to access call controls and administrative menus
- Intuitive user interface

#### **TECHNOLOGY**

- Capacitive touch sensor supports
  multi-touch functionality
- Direct API command through network
- LCD panel with LED backlighting
- IPS (In-Plane Switching)

#### **ELECTRICAL**

- Power over Ethernet (PoE), compatible with IEEE 802.3af Class 3
- Low-power sleep mode

#### WARRANTY

- · One-year return to factory parts and labor
- 90-day software warranty

#### **PART NUMBER**

• 2200-30760-001

## LEARN MORE

For more information on Poly TC8